

Type

Uula Floor Paint is a beautiful and traditional paint for floors, furniture and all surfaces in need of a durable paint surface. Uula Floor Paint is made of natural resins and linseed oil alkyd. Aromatic-free hydrocarbon solvent.

Intended use

Interior wood and wood-fibre board.
Suitable also for different stone surfaces in dry interiors.

Technical qualities

Gloss grade: Semi-glossy.
Density 1.12 kg/L.
VOC emissions under 300g/l.
EU VOC -limit value: (cat A/i) 300g/L (2010).

Colours

See Uula Traditional Colour Chart, special tints can be made to order.
Uula Linseed Oil Paint is tinted with colour pastes made from genuine colour pigments.

Application & conditions

Paint brush, mohair roller or lacquer spatula.
The surface to be painted must be dry, the humidity of the wood below 15 %, the relative air humidity below 80 % and the temperature at least +10°C.

Drying time

At 20°C and <50 % relative humidity: Tack-free in 6 hours.
A new coat can be applied after 24 hours, hardening continues for one month.
Note: Heat and light accelerate drying.

Coverage

10–12 m²/L.

Thinner

Uula Universal Thinner

Cleaning of equipment

Clean the equipment with Uula Universal Thinner or petroleum spirit and rinse with soap and water.

Container sizes

0.9 L, 2.7 L, 9 L

Storage & disposal

Keep in a cool and dry place. Keep out of the reach of children. Does not freeze.
Dry and empty containers can be taken to a refuse dump.
Liquid waste must be taken to a municipal hazardous waste collection point.

Fire classification

Non-flammable.
Caution: Linseed oil on cleaning rags etc. may catch fire by itself. Oily rags and cloths etc. should be burned or rinsed in water before putting into refuse bins.

Painting instructions

Preparations

Remove dust from the surface to be treated. Remove loose old paint with a scraper and sand the surface. Brush off dust, fill cracks and holes, remove nail heads. Wash dirty surfaces with Uula Washing Agent following the instructions. Allow to dry thoroughly before treating.

Undercoat

Paint new wood floors with Uula Floor Paint that has been thinned 20 % and previously painted floors with Uula Floor Paint that has been thinned 10 % with Uula Universal Thinner. Paint thin layers and let it dry.

Finishing coat

Paint 1–2 coats with Uula Floor Paint and thin with Uula Universal Thinner if necessary.

Further treatment of the surface

Be really careful with all painted surfaces during the first month. Clean the surface only with soft rags and sponges that do not scratch the surface. Use only neutral washing agents. Rinse the surfaces carefully.

Points to note

- *Reserve enough paint for a large surface in order to avoid potential colour variations in different batches.
- *The paint must always be stirred well before and during use.
- *It is distinctive of oil paints in light colours to turn yellowish in the dark.
- *In all cases of uncertainty, please contact the manufacturer or a competent distributor before use.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuoite Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.