

Type

For thinning of exterior paints. The Oil Paint Thinner is made of boiled linseed oil (varnish, 35 %) and aromatic-free hydrocarbon solvent (65 %).

Intended use

For thinning of Uula Linseed Oil Paint, Uula Matt Linseed Oil Paint and Uula Graphite Paint.

Technical qualities

Density approx. 0.85kg/L.

Container size

1 L, 3 L and 10 L.

Storage & disposal

Keep in a cool place. Keep out of the reach of children. Do not allow to freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point

Fire classification

Non-flammable.

Caution: Linseed oil on cleaning rags etc. may catch fire by itself. Oily rags and cloths etc. should be burned or rinsed in water before putting into refuse bins.

In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.