

## Type

Fast drying and odourless glazing paint for interior use. Does not contain plastic agents. Ilona glazing paint leaves the grains of the wood visible and gives a surface that protects from moisture and dirt in both dry and damp conditions indoors.

## Intended use

For old and new untreated wood surfaces and surfaces that have been treated with glazing agents that do not form a hard coating, e.g. ceilings, wall panels, doors, window frames and furniture indoors.

## Technical qualities

Gloss grade: Silky matt.

Density 1.05 kg/L.

Emission class M1 in building materials.

Wet abrasion resistance: over 5000 strokes. Washable.

Does not contain any VOC.

Non-flammable.

## Colours

Colourless, can be tinted according to the translucent colours of Uula interior colour chart. Can also be tinted according to most common colour charts.

## Application & conditions

Lacquer brush, levelling paint brush, ordinary paint brush or high-pressure paint sprayer.

The surface to be painted must be dry, the relative air humidity below 80 % and the temperature at least +10°C.

## Drying time

Tack-free in approx. 30 minutes. A new coat of paint can be applied after 2 hours. (At 20°C and 80 % relative humidity).

## Coverage

Planed/smooth timber 12–15 m<sup>2</sup>/L, sawn/porous timber 6–10 m<sup>2</sup>/L.

## Thinner

Water

## Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

## Container sizes

0.9 L, 2.7 L, 9 L

## Storage & disposal

Keep in a cool and dry place. Do not allow to freeze!

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point



## **Painting instructions**

### **Preparation**

Remove dust from the surface to be treated. Wash dirty surfaces with Uula Washing Agent following the instructions. Allow to dry thoroughly before treating.

### **Colourless treatment**

Treat the surface with colourless Ilona Glazing Paint 1–3 times.  
Sand the surface in between treatments and remove dust.

### **Coloured treatment**

Treat the surface with Ilona Glazing Paint 1–2 times to the desired opacity.  
To enhance endurance treat the surface 1–2 times with colourless Ilona Glazing Paint.

### **Further treatment of the surface**

Be really careful with all painted surfaces during the first month.  
Clean the surface only with soft rags and sponges that do not scratch the surface.  
Use only neutral washing agents. Rinse the surfaces carefully.

### **Points to note**

- \*Stir Ilona Glazing Paint thoroughly before and during use
- \*Reserve enough paint for a large surface in order to avoid potential colour variations in different batches.
- \*The colour of the surface to be treated must be taken into consideration when choosing translucent treatment agent. A small colour sample before the actual treatment is recommended.
- \*In all cases of uncertainty, please contact the manufacturer or a competent distributor before use.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.