

## **Type**

Uula Floor Paint is a beautiful and traditional paint for floors, furniture and all surfaces in need of a durable paint surface. Uula Floor Paint is made of natural resins and linseed oil alkyd. Aromatic-free hydrocarbon solvent.

## **Intended use**

Interior wood and wood-fibre board.  
Suitable also for different stone surfaces in dry interiors.

## **Technical qualities**

Gloss grade: Semi-matt.  
Density 1.08 kg/L.  
VOC emissions under 350g/l.  
EU VOC -limit value: (cat A/i) 500g/L (2010).

## **Colours**

White and tints made to A- and C-bases.  
Can be tinted according to most common colour charts.

## **Application & conditions**

Paint brush, mohair roller or lacquer spatula.  
The surface to be painted must be dry, the humidity of the wood below 15 %, the relative air humidity below 80 % and the temperature at least +10°C.

## **Drying time**

At 20°C and <80 % relative humidity: Tack-free in 6 hours.  
A new coat can be applied after 24 hours, hardening continues for one month.  
Note: Heat and light accelerate drying.

## **Coverage**

10–12 m<sup>2</sup>/L.

## **Thinner**

Uula Universal Thinner

## **Cleaning of equipment**

Clean the equipment with Uula Universal Thinner or petroleum spirit and rinse with soap and water.

## **Container sizes**

0.9 L, 2.7 L, 9 L

## **Storage & disposal**

Keep in a cool and dry place. Keep out of the reach of children. Does not freeze.  
Dry and empty containers can be taken to a refuse dump.  
Liquid waste must be taken to a municipal hazardous waste collection point.

## **Painting instructions**

### **Preparations**

Remove dust from the surface to be treated. Remove loose old paint with a scraper and sand the surface. Brush off dust, fill cracks and holes, remove nail heads. Wash dirty surfaces with Uula Washing Agent following the instructions. Allow to dry thoroughly before treating.

### **Undercoat**

Paint new wood floors with Uula Floor Paint that has been thinned 20 % and previously painted floors with Uula Floor Paint that has been thinned 10 % with Uula Universal Thinner. Paint thin layers and let it dry.

### **Finishing coat**

Paint 1–2 coats with Uula Floor Paint and thin with Uula Universal Thinner if necessary.

### **Further treatment of the surface**

Be really careful with all painted surfaces during the first month. Clean the surface only with soft rags and sponges that do not scratch the surface. Use only neutral washing agents. Rinse the surfaces carefully.

### **Points to note**

- \*Reserve enough paint for a large surface in order to avoid potential colour variations in different batches.
- \*The paint must always be stirred well before and during use.
- \*It is distinctive of oil paints in light colours to turn yellowish in the dark.
- \*In all cases of uncertainty, please contact the manufacturer or a competent distributor before use.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.