

iNTO PANEL PAINT

UULA COLOR 2021

Type

Fast-drying, breathable and odourless water-based oil paint for interior wall and ceiling panelling. iNTO Panel Paint has excellent coverage and adhesive qualities due to which no primer is required. Contains no plastic agents. The binder is made up of renewable natural oils.

Intended use

Untreated or previously painted panel, wood and board surfaces such as walls and ceilings in dry interior spaces.

Technical qualities

Gloss level: semi-matt

Density approx. 1.3 kg/L

Contains no methylisothiazolinone (MIT)

Contains no volatile organic compounds (VOC)

Emission class M1 in building materials.

Wet abrasion resistance: SFS-EN 13300 class 1, ISO 11998

Washability class: SFS 3755: over 5000 brushes



Colours

Base A (white). Machine tinting. May be tinted to most common colour charts.

Application & conditions

Ordinary paint brush, roller or low-pressure paint sprayer. The surface to be painted must be dry, the relative air humidity below 80 % and the temperature at least +10°C.

Drying time

Touch dry in approx. 30 minutes. Ready for a re-coat in 2 hours.
(+20°C and relative air humidity below 80%)

Coverage

Approx 7 m²/L depending on the roughness and porosity of the surface.

Thinner

Water

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Container sizes

0.9 L, 2.7 L and 9 L.

Storage and disposal

Storage in a cool and dry place. DO NOT ALLOW TO FREEZE! Dry and empty containers can be recycled. Liquid waste must be taken to a municipal hazardous waste collection point.

Painting instructions

Unpainted surface

Clean the surface of dust.

Wash dirty surfaces with Uula Washing Agent following the instructions.

Allow to dry thoroughly before painting.

Level cracks and holes with filler if necessary.

Prime new surfaces with INTO Primer.

Apply two coats of INTO Panel Paint. Thin with water if necessary.

Previously painted or varnished surfaces

Remove peeling and flaky old paint.

Sand a glossy or hard surface with a sandpaper to ensure adhesion.

Wash dirty surfaces with Uula Paint Washing Agent following the instructions.

Allow to dry thoroughly before painting.

Level cracks and holes with filler if necessary.

Prime bare patches with INTO Interior Primer if necessary.

Apply two coats of INTO Interior Paint. Thin with water if necessary.

Care instructions

Treat painted surfaces with care during the first month.

Clean with soft cloths and sponges that do not scratch the surface.

Use neutral washing agents only. Rinse the surface thoroughly.

Tips for painting

Stir the paint thoroughly before use and during painting.

Reserve and mix enough paint for a large surface to avoid potential colour variations in different batches.

Paint a test patch to ensure that the colour is correct.

There may be subtle variation in shade depending on the gloss level of paints, tinting pastes, tinting machines and methodology.

Always choose paint in the space and lighting it is intended for. Lighting and gloss level of the paint affect the perception of colour.

Apply paint generously.

If uncertain, get in touch with the manufacturer of the paint or with a competent retailer before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.